



# TUCK TAPE® CARTON SEALING TAPE

## RETAIL PACKAGING TAPES

Discover a versatile range of Tuck Tape® packing and shipping tapes designed to meet all your box sealing needs. Whether you're securing light to heavy packages, repairing cartons, or bundling shipments, each of these products offers dependable adhesion and durability. With superior resistance to yellowing, aging, weathering, and UV light, our tapes ensure your packages remain secure and protected throughout transit and storage. Enjoy reliable closures and peace of mind, no matter the application or box weight.



## FEATURES & BENEFITS

### UTILITY PACKING TAPE



For boxes up to 20 pounds



Resists yellowing, aging, weathering and UV light

### ADVANCED PACKAGING TAPE



For light to medium weight box sealing, package repair and bundling applications



Designed to adhere to a variety of corrugated and linerboard boxes

### PREMIUM SHIPPING TAPE



For heavy boxes up to 50 pounds



Crystal clear & resists yellowing and UV light



Premium performance for rough shipping and stress



All-temperature box sealing performance

## PRODUCT ATTRIBUTES

CHARACTERISTICS	Utility Packing Tape			
Product Code	343004850	34360850	34200	344004850
Dimensions	48mm x 50m	48mm x 50m	48mm x 50m	48mm x 50m
Rolls/Pack	1	6	2	4
Rolls/Case	48	36	6 boxes	48
Product UPC	067735343000	067735343604	067735342003	067735344007
Thickness (mil)	1.75	1.75	1.75	1.75
Tensile (lb/in)	23	23	23	23
Adhesion (oz/in)	16	16	16	16
Elongation (%)	80	80	80	80
Case UPC	10067735343007	10067735343601	10067735342000	10067735344004



## PRODUCT APPLICATIONS

- Box sealing
- Mailroom
- Parcel shipping
- Package repair
- Patching
- Bundling

## MARKETS

- Consumer Retail
- E-commerce
- Moving and Storage
- Manufacturing

CHARACTERISTICS	Advanced Packaging Tape		Premium Shipping Tape	
Product Code	3530048100	3536048100	346004850	346404850
Dimensions	48mm x 100m	48mm x 100m	48mm x 50m	48mm x 50m
Rolls/Pack	1	6	1	4
Rolls/Case	12	36	48	12
Product UPC	067735353009	067735353603	067735346001	067735346407
Thickness (mil)	1.6	1.6	2.7	2.7
Tensile (lb/in)	25	25	28	28
Adhesion (oz/in)	32	32	21	21
Elongation (%)	80	80	150	150
Case UPC	10067735330095	10067735353600	10067735346008	10067735346404



Scan for more info or visit [www.tuckbuilding.com](http://www.tuckbuilding.com)

